

Section name references in L^AT_EX*

Sebastian Rahtz

2012/07/28

Documentation overview for `hyperref`

The documentation for package `hyperref` consists of several files:

Manual The **USER MANUAL** (also available as HTML).

README The **README** file (also available as text file). Here information is collected that is not yet in the manual: new features, package compatibility, limitations, known problems, ...

ChangeLog This file records the version history (also available as text file).

Options This file provides a short option summary.

Bookmark talk, slides Slides for the talk “PDF information and navigation elements with hyperref, pdfTeX and thumbpdf” at EuroTeX 1999.

Bookmark talk, paper The paper version of the talk.

Source code documentation:

hyperref.dtx This is the source code documentation for hyperref.

backref.dtx “Back referencing from bibliographical citations”

☞ **nameref.dtx** “Section name references in L^AT_EX” (this file)

Contents

1	Introduction	2
2	History	2
3	Implementation	2
3.1	\label stuff	3
3.2	Changes of section macros	5
3.2.1	Class beamer	7
3.2.2	Theorems	8
3.3	Referencing stuff	8
3.4	Usage and frontend	10
3.5	Package ifthen support	11
3.6	Compatibility with varioref	11
3.7	Support for listings	13

*This file has version number v2.41, last revised 2012/07/28.

1 Introduction

Cross-referencing to include the *name* of the section, rather than just the number or page. This works by redefining some of the inside L^AT_EX macros, so it is vulnerable to future changes.

2 History

Sebastian Rahtz, for Lou Burnard, March 15th 1994;
 SPQR CERN July 1994;
 Last mod. Sept. 3th MG;
 Sept. 19th SPQR;
 April 11th 1995 SPQR (added section formatting hook);
 April 14th 1995 SPQR (compatibility with hyperref);
 June 22 1995 SPQR (removed typeout from Sectionformat);
 September 22 1997 added variorref hacks by Corey Minyard;
 September 28th changes by David Carlisle.
 More recent changes are recorded in ChangeLog.

The versions before 2009/11/27 v2.32 did not expand the title strings (of \section, \caption, ...). Then the behaviour switched to expanding, because this allows to remove unwanted macros (\label, ...). Despite this method is used in package titleref and class memoir, the first feedbacks let me conclude that this is not robust enough. Therefore I wrote package gettitlestring that uses the non-expanding method as default. It also allows me to use this package in package zref-titleref. See the package documentation of package gettitlestring how to change the method. It also provides a hook to remove additional unwanted macros, not supported by the package. Example:

```
\usepackage{gettitlestring}
\GetTitleStringDisableCommands{%
  \let\mylabel\@gobble
  \renewcommand\myindex[2]{}%
}
```

3 Implementation

```
1 {*package}
2 \RequirePackage{refcount}[2006/02/12]
3 \RequirePackage{gettitlestring}[2009/12/18]
4 \RequirePackage{ltxcmds}[2009/12/12]
```

We redefine \label so that it also writes the name of the current section to the .aux file; if the name ends in a dot, we zap it. To allow for the hyperref package, also write fourth and fifth fields (empty by default; used for cross-ref name, and file).

```
\NR@strip@period
5 \def\NR@strip@period#1.\ltx@empty#2\@nil{#1}
6 \def\NR@sanitize@labelname{%
7   \onelevel@sanitize\@currentlabelname
8   \edef\@currentlabelname{%
```

```

9   \expandafter\NR@strip@period\@currentlabelname
10  \ltx@empty.\ltx@empty\@nil
11 }%
12 }

```

3.1 \label stuff

Here is tested, whether package showkeys is loaded. But if option final is used, the macros of showkeys are not defined, so we have to check an additional test.

```

\ifNR@showkeys
13 \newif\ifNR@showkeys
14 \NR@showkeysfalse
15 \@ifpackage{showkeys}{%
16 \begingroup
17 \ifundefined{SK@\label}{%
18 }{%
19 \global\NR@showkeystrue
20 }%
21 \endgroup
22 }{%
\label@hook
23 \providecommand*\label@hook{}%
24 \ltx@GlobalAppendToMacro{\label@hook}{%
25 \NR@sanitize@labelname
26 }

\label
27 \def\label#1{%
28 \bphack
29 \begingroup
30 \def\label@name{#1}%
31 \label@hook
32 \protected@write\auxout{}{%
33 \string\newlabel{#1}{%
34 {\@currentlabel}%
35 {\thepage}%
36 {\@currentlabelname}%
37 {\@currentHref}%
38 }%
39 }%
40 \endgroup
41 \esphack
42 }%
43 \ifNR@showkeys
44 \def\label#1{%
45 \bphack
46 \SK@\SK@\label{#1}%
47 \begingroup
48 \def\label@name{#1}%
49 \label@hook
50 \protected@write\auxout{}{%
51 \string\newlabel{#1}{%
52 {\@currentlabel}%
53 {\thepage}%
54 {\@currentlabelname}%

```

```

55      {\@currentHref}{}%
56      }%
57      }%
58  \endgroup
59  \esphack
60 }%
61 \fi

\ltx@label
62 \let\ltx@label\label

```

Needed for the *subeqnarray* package.

```

\slabel
63 \@ifundefined{slabel}{}{%
64 \def\slabel{\#1}{%
65   \bsphack
66   \if@filesw
67     \begingroup
68       \def\labelname{\#1}%
69       \label@hook
70       \let\thepage\relax
71       \def\protect{\noexpand\noexpand\noexpand}%
72       \edef\@tempa{%
73         \write\auxout{%
74           \string\newlabel{\#1}{%
75             {\thesubequation}%
76             {\thepage}%
77             {\@currentlabelname}%
78             {\@currentHref}{}%
79           }%
80         }%
81       }%
82     \expandafter\endgroup
83     \atempa
84     \ifnobreak\ifvmode\nobreak\fi\fi
85   \fi
86   \esphack
87 }%
88 }

```

Overload an AMS L^AT_EX command, which uses *\newlabel*. Sigh!

```

\@writetocindents@
89 \def\@writetocindents@{%
90 \begingroup
91 \@for\@tempa:=-1,0,1,2,3\do{%
92   \immediate\write\auxout{%
93     \string\newlabel{tocindent\@tempa}{%
94       \csname r@tocindent\@tempa\endcsname{}{}{}{}%}
95   }%
96 }%
97 }%
98 \endgroup
99 }

```

3.2 Changes of section macros

Add to the underlying section heading macros so that they note the section name for use by label.

If a section heading or the like has a `\label` in it, we need to extract it, or subsequent processing breaks.

```
\NR@gettitle
100 \def\NR@gettitle#1{%
101   \GetTitleString{#1}%
102   \let\@currentlabelname\GetTitleStringResult
103 }
```

First the numbered sections. While we are about it, put in a useful section formatting macro.

```
\NR@sect
104 \let\NR@sect\@sect
105 \newcounter{section@level}

\@sect
106 \def\@sect#1#2#3#4#5#6[#7]#8{%
107   \setcounter{section@level}{#2}%
108   \NR@gettitle{#7}%
109   \NR@sect{#1}{#2}{#3}{#4}{#5}{#6}[{#7}]{\Sectionformat{#8}{#2}}%
110 }
```

and now the unnumbered ones

```
\NR@ssect
111 \let\NR@ssect\@sect

\NR@ssect
112 \def\@ssect#1#2#3#4#5{%
113   \NR@gettitle{#5}%
114   \NR@ssect{#1}{#2}{#3}{#4}{\Sectionformat{#5}{#1}}%
115 }
```

Support for class memoir.

```
116 \ltx@ifundefined{ifheadnameref}{%
117 }{%
118   \ltx@ifundefined{M@sect}{%
119   }{%
120     \let\NRorg@M@sect\@sect
121     \def\@sect#1#2#3#4#5#6[#7]#8{%
122       \ifheadnameref
123         \NR@gettitle{#8}%
124       \else
125         \NR@gettitle{#7}%
126       \fi
127       \NRorg@M@sect{#1}{#2}{#3}{#4}{#5}{#6}[{#7}][{#8}]%
128     }%
129   }%
130 }
```

Parts and chapters are treated differently. sigh. `\@part` and `\@spart` are `\long` because of class memoir.

```

131 \let\NR@part\@part
132 \long\def\@part[#1]{%
133   \NR@gettitle{#1}%
134   \NR@part[{#1}]{#2}%
135 }
136 \let\NR@spart\@spart
137 \long\def\@spart#1{%
138   \NR@gettitle{#1}%
139   \NR@spart{#1}%
140 }
141 \let\NR@chapter\@chapter
142 \def\@chapter[#1]{%
143   \NR@gettitle{#1}%
144   \NR@chapter[{#1}]{#2}%
145 }
146 \ifclassloaded{memoir}{%
147   \ltx@ifUndefined{ifheadnameref}{%
148     }{%
149       \def\@chapter[#1]{%
150         \ltx@ifUndefined{ch@pt@c}{%
151           \NR@gettitle{#1}%
152         }{%
153           \ifx\ch@pt@c\ltx@empty
154             \NR@gettitle{#2}%
155           \else
156             \def\NR@temp{#1}%
157             \ifx\NR@temp\ltx@empty
158               \expandafter\NR@gettitle\expandafter{\ch@pt@c}%
159             \else
160               \ifheadnameref
161                 \NR@gettitle{#1}%
162               \else
163                 \expandafter\NR@gettitle\expandafter{\ch@pt@c}%
164               \fi
165             \fi
166           \fi
167         }%
168       \NR@chapter[{#1}]{#2}%
169     }%
170   }{%
171 }
172 \let\NR@schapter\@schapter
173 \def\@schapter#1{%
174   \NR@gettitle{#1}%
175   \NR@schapter{#1}%
176 }
```

Captions

```

177 \AtBeginDocument{%
178   \ifpackagelocked{hyperref}{%
179     \ifpackagelater{hyperref}{2009/12/05}{%
180       \firstofone
181     }{%
182       \let\NR@@caption\caption
183       \long\def\@caption[#1]{%
```

```

184     \NR@getttitle{#2}%
185     \NR@@caption{#1}{#2}%
186   }%
187 }%
188 \c@ifpackageloaded{longtable}{%
189   \let\NRorg@LT@c@option\LT@c@option
190   \def\LT@c@option#1[#2]#3{%
191     \NRorg@LT@c@option{#1}[#2]{#3}%
192     \def\@tempa{#2}%
193     \ifx\@tempa\@empty
194     \else
195       \NR@getttitle{#2}%
196     \fi
197   }%
198 }{%

```

Environment ‘description’.

```

199 \ltx@IfUndefined{descriptionlabel}{%
200 }{%
201   \let\NRorg@descriptionlabel\descriptionlabel
202   \def\descriptionlabel#1{%
203     \NR@getttitle{#1}%
204     \NRorg@descriptionlabel{#1}%
205   }%
206 }%
207 }

```

Compatibility for package titlesec.

```

208 \AtBeginDocument{%
209   \c@ifpackageloaded{titlesec}{%
210     \let\NRorg@ttl@sect@i\ttl@sect@i
211     \def\ttl@sect@i#1#2[#3]#4{%
212       \NR@getttitle{#4}%
213       \NRorg@ttl@sect@i{#1}{#2}{#3}{#4}%
214     }%
215   }{%
216 }

```

3.2.1 Class beamer

```

217 \c@ifclassloaded{beamer}{%
218   \def\NR@PatchBeamer#1{%
219     \expandafter\let\csname NRorg@beamer@#1\expandafter\endcsname
220           \csname beamer@#1\endcsname
221     \begingroup
222     \edef\x{\endgroup
223       \long\def\expandafter\noexpand\csname beamer@#1\endcsname
224         [####1]{% hash-ok
225           \noexpand\NR@getttitle{####1}%
226           \expandafter\noexpand\csname NRorg@beamer@#1\endcsname
227             [####1]}%
228         }%
229       }%
230     \x
231   }%
232   \NR@PatchBeamer{section}%
233   \NR@PatchBeamer{subsection}%
234   \NR@PatchBeamer{subsubsection}%

```

```

235 }{ }

3.2.2 Theorems

236 \ltx@IfUndefined{@opargbegintheorem}{}{%
237   \let\NRorg@opargbegintheorem\@opargbegintheorem
238   \def\@opargbegintheorem#1#2#3{%
239     \NR@gettitle{#3}%
240     \NRorg@opargbegintheorem{#1}{#2}{#3}%
241   }%
242 }
243 \AtBeginDocument{%
244   \ifpackageloaded{amsthm}{%
245     \let\NRorg@begintheorem\@begintheorem
246     \begingroup
247       \edef\x{macro:\string#1\string#2[\string#3]}%
248       \@onelvel@sanitize\x
249       \def\y#1->#2\@nil{#1}%
250       \edef\z{\expandafter\y\meaning\@begintheorem->\@nil}%
251       \@onelvel@sanitize\z
252     \expandafter\endgroup
253     \ifx\x\z
254       \def\@begintheorem#1#2[#3]{%
255         \NR@gettitle{#3}%
256         \NRorg@begintheorem{#1}{#2}{#3}%
257       }%
258     \fi
259   }{}}%
260 }

```

3.3 Referencing stuff

We default the label and hypertext reference to be empty.

```

261 \providecommand*{\@currentlabelname}{}
262 \providecommand*{\@currentHref}{}

```

Since the second part of the preserved reference now has five parts (number, page, name, hypertext reference and file), we need extra utility macros:

```

\@firstoffive
263 \long\def\@firstoffive#1#2#3#4#5{#1}

\@secondoffive
264 \long\def\@secondoffive#1#2#3#4#5{#2}

\@thirdoffive
265 \long\def\@thirdoffive#1#2#3#4#5{#3}

\@fourthoffive
266 \long\def\@fourthoffive#1#2#3#4#5{#4}

\@offive
267 \long\def\@fifthoffive#1#2#3#4#5{#5}

```

We have to redefine `\ref` and `\pageref` to know about extra reference elements. Make them robust, and compatible with Babel. The Babel switch is mimicked if not already defined. Some support for package `showkeys` is implemented. If option `notref` of that package is set, `\SK@ref` has the meaning of `\@empty`.

```

\@safe@activestru $\backslash$ 
268 \providecommand*{\@safe@activestru}{}
```

```

\@safe@activesfa $\backslash$ 
269 \providecommand*{\@safe@activesfa}{}
```

```

\NR@setref
270 \def\NR@setref#1{%
271   \begingroup
272     \@safe@activestru
273     \expandafter
274   \endgroup
275   \expandafter\NR@setref\csname r@#1\endcsname
276 }
```

```

\NR@setref
277 \def\NR@setref#1{%
278   \ifx\@undefined#1%
279     \let#1\relax
280   \fi
281   \setref#1%
282 }
```

```

\T@ref
283 \def\T@ref#1{%
284   \NR@setref{#1}\@firstoffive{#1}%
285 }
```

```

\T@pageref
286 \def\T@pageref#1{%
287   \NR@setref{#1}\@secondoffive{#1}%
288 }
```

```

289 \ifNR@showkeys
290   \ifx\SK@ref\empty
291   \else
```

```

\T@ref
292 \def\T@ref#1{%
293   \@safe@activestru
294   \SK@\SK@ref{#1}%
295   \@safe@activesfa
296   \NR@setref{#1}\@firstoffive{#1}%
297 }
```

```

\T@pageref
298 \def\T@pageref#1{%
299   \@safe@activestru
300   \SK@\SK@ref{#1}%
301   \@safe@activesfa
302   \NR@setref{#1}\@secondoffive{#1}%
303 }
```

```

304 \fi
305 \fi

```

Package `hyperref` uses its own definitions of `\ref` and `\pageref` because it extends the syntax by the star form. `\DeclareRobustCommand` is used by `hyperref`. Package `nameref` can be loaded before, after `hyperref` or after `hyperref`'s definitions in `\AtBeginDocument`.

```
306 \@ifpackageloaded{hyperref}{%
307 }{%
```

```
\ref
308 \DeclareRobustCommand{\ref}{\T@ref}%
\nameref
309 \DeclareRobustCommand{\nameref}{\T@nameref}%
310 }
```

3.4 Usage and frontend

Access the (third) name part with `\nameref`:

```
\T@nameref
311 \def\T@nameref#1{%
312   \begingroup
313   \let\label\@gobble
314   \NR@setref{\#1}\@thirdoffive{\#1}%
315   \endgroup
316 }%
317 \ifNR@showkeys
318   \ifx\SK@ref\empty
319   \else
320     \def\T@nameref#1{%
321       \csname\active@true\endcsname
322       \SK@\SK@{\ref{\#1}}%
323       \csname\active@false\endcsname
324     \begingroup
325       \let\label\@gobble
326       \NR@setref{\#1}\@thirdoffive{\#1}%
327     \endgroup
328   }%
329 \fi
330 \fi

331 %\ifclassloaded{memoir}{%
332 %  \ltx@IfUndefined{@mem@titlerefno link}\ltx@secondoftwo{%
333 %    \ltx@IfUndefined{@mem@titleref}\ltx@secondoftwo\ltx@firstoftwo
334 %  }%
335 %}\ltx@secondoftwo
336 %}%
337 % \DeclareRobustCommand*\nameref{%
338 %   \csname\ifstar\mem@titlerefno link\endcsname\mem@titleref
339 % }%
340 %}%

\nameref
341 \DeclareRobustCommand*\nameref{%
342   \csname\ifstar\T@nameref\T@nameref\endcsname
343 }%
344 %}
```

```

\Nameref An extended form which gives title and page number.
345 \def\Nameref#1{'\nameref{\#1}' on page-\pageref{\#1} }

\Sectionformat The default for \Sectionformat
346 \providecommand\Sectionformat[2]{\#1}

```

3.5 Package ifthen support

Package ifthen's `\isodd` does not work with `\pageref` because of the extra link and the star form. Therefore we need an expandable variant.

Unfortunately there is no hook in `\ifthenelse` in order to provide expandable versions without link of `\ref` and `\pageref`. As possible target I could only find `\begingroup`:

```

347 \@ifpackageloaded{ifthen}{%
348   \let\NROrg@ifthenelse\ifthenelse
349   \def\ifthenelse{%
350     \let\begingroup\NR@TE@begingroup
351     \NROrg@ifthenelse
352   }%
353   \let\NROrg@begingroup\begingroup
354   \def\NR@TE@begingroup{%
355     \let\begingroup\NROrg@begingroup
356     \begingroup
357     \def\ref##1{\getrefbykeydefault{\##1}{}{??}}%
358     \def\pageref##1{\getrefbykeydefault{\##1}{page}{0}}%
359   }%
360 }{%

```

3.6 Compatibility with variorref

[This section was derived by Corey Minyard `minyard@acm.org` from the variorref package]

```

361 \AtBeginDocument{%
362   \ifx\csname @@vpageref\endcsname\relax
363   \else
364     \def\@@vpageref#1[#2]#3{%
365       \begingroup
366         \csname @safe@activestrue\endcsname
367         \edef\x{#3}%
368         \onelevel@sanitize\x
369         \toks@{%
370           \NR@vpageref{\#1}[{\#2}]%
371         }%
372         \edef\x{\endgroup
373           \the\toks@\x}%
374       }%
375       \x
376     }%
377     \def\NR@vpageref#1[#2]#3{%
378       \leavevmode\unskip
379       \global\advance\c@vrcnt\@ne
380       \@ifundefined{r@\the\c@vrcnt @vr}%
381         {\@namedef{r@\the\c@vrcnt @vr}{{??}{??}{}}{}}{}}{%
382       \edef\@tempa{%
383         \expandafter\expandafter\expandafter
384         \secondoffive\csname r@\the\c@vrcnt @vr\endcsname

```

```

385      }%
386      \@ifundefined{r@\the\c@vrcnt @xvr}%
387      { \@namedef{r@\the\c@vrcnt @xvr}{\{\?\?\}\{\?\?\}\{\}\{\}\{\}}\{\}%
388      \edef\@tempb{%
389          \expandafter\expandafter\expandafter
390          \@secondoffive\csname r@\the\c@vrcnt @xvr\endcsname
391      }%
392      {\%
393          \let\@currentlabel\empty
394          \expandafter\label\expandafter{\the\c@vrcnt @xvr}%
395      }%
396      \ifx\@tempa\@tempb
397      \else
398          \vref@err{%
399              \noexpand\vref at page boundary %
400              \@tempb-\@tempa\space (may loop)%
401          }%
402      \fi
403      \@ifundefined{r@##3}{\@namedef{r@##3}{\{\?\?\}\{\?\?\}\{\}\{\}\{\}}\{\}%
404      \edef\thevpagerefnum{%
405          \expandafter\expandafter\expandafter
406          \@secondoffive\csname r@##3\endcsname
407      }%
408      \ifx\thevpagerefnum\@undefined
409          \space
410      \else
411          \vref@space
412      \fi
413      \ifx\@tempa\thevpagerefnum
414          #1%
415      \else
416          #2%
417          \is@pos@number\thevpagerefnum{%
418              \is@pos@number\@tempa{%
419                  \@tempcnta\@tempa
420                  \advance\@tempcnta\@ne
421              }{%
422                  \@tempcnta\maxdimen
423              }%
424              \ifnum \thevpagerefnum =\@tempcnta
425                  \ifodd\@tempcnta
426                      \if@twoside
427                          \reftextfaceafter
428                      \else
429                          \reftextafter
430                      \fi
431                  \else
432                      \reftextafter
433                  \fi
434              \else
435                  \advance\@tempcnta-2 %
436                  \ifnum \thevpagerefnum =\@tempcnta
437                      \ifodd\@tempcnta
438                          \reftextbefore
439                      \else
440                          \if@twoside
441                              \reftextfacebefore

```

```

442      \else
443          \ref{textbefore}
444      \fi
445      \fi
446      \else
447          \ref{textfaraway}{#3}%
448      \fi
449      \fi
450  }{%
451      \ref{textfaraway}{#3}%
452  }%
453 \fi
454 {%
455     \let\@currentlabel\@empty
456     \expandafter\label\expandafter{\the\c@vrcnt \vr}%
457 }%
458 }%
459 \DeclareRobustCommand\vnameref[1]{%
460     \unskip~\nameref{#1}%
461     \vphantom{\unskip}\vphantom{#1}%
462 }%
463 \fi
464 }

465 \@ifundefined{@Refstar}{%
466 \def\T@Ref#1{%
467     \NR@setref{#1}\NR@MakeUppercaseFirstOfFive{#1}%
468 }%
469 \def\NR@MakeUppercaseFirstOfFive#1#2#3#4#5{%
470     \MakeUppercase#1%
471 }%
472 }{%
473 \AtBeginDocument{%
474     \ifpackageloaded{variorref}{%
475         \ifundefined{@Refstar}{%
476             \DeclareRobustCommand*\Ref[1]{%
477                 \T@Ref{#1}%
478             }%
479         }{%
480     }{%
481 }%
482 \AtBeginDocument{%
483     \ifpackageloaded{listings}{%
484         \let\NROrg@lst@MakeCaption\lst@MakeCaption
485         \def\lst@MakeCaption{%
486             \ifx\lst@label\@empty
487             \else
488                 \let\@currentlabelname\lst@caption
489             \fi
490             \NROrg@lst@MakeCaption
491         }%
492     }{%
493 }
494 
```

3.7 Support for listings

```

482 \AtBeginDocument{%
483     \ifpackageloaded{listings}{%
484         \let\NROrg@lst@MakeCaption\lst@MakeCaption
485         \def\lst@MakeCaption{%
486             \ifx\lst@label\@empty
487             \else
488                 \let\@currentlabelname\lst@caption
489             \fi
490             \NROrg@lst@MakeCaption
491         }%
492     }{%
493 }
494 
```

4 Index

Numbers written in italic refer to the page where the corresponding entry is described; numbers underlined refer to the code line of the definition; numbers in roman refer to the code lines where the entry is used.

Symbols \@c@vpageref 364 \@auxout 32, 50, 73, 92 \@begintheorem 245, 250, 254 \@bsphack 28, 45, 65 \@caption 182, 183 \@chapter 141, 142, 149 \@currentHref 37, 55, 78, 262 \@currentlabel 34, 52, 393, 455 \@currentlabelname 7, 8, 9, 36, 54, 77, 102, 261, 488 \@empty 193, 290, 318, 393, 455, 486 \@esphack 41, 59, 86 \@fifthoffive 267 \@firstoffive 263, 284, 296 \@firstofone 179, 180 \@for 91 \@fourthoffive 266 \@gobble 179, 313, 325 \@ifclassloaded 146, 217, 331 \@ifpackagelater 179 \@ifpackageloaded 15, 178, 188, 209, 244, 306, 347, 474, 483 \@ifstar 338, 342 \@ifundefined 17, 63, 380, 386, 403, 465, 475 \@mem@titleref 338 \@mem@titlerefno link 338 \@namedef 381, 387, 403 \@ne 379, 420 \@nil 5, 10, 249, 250 \@offive 267 \@onelvel@sanitize 7, 248, 251, 368 \@opargbegintheorem 237, 238 \@part 131, 132 \@safe@activesfalse 269, 295, 301, 323 \@safe@activesttrue 268, 272, 293, 299, 321	\@schapter 172, 173 \@secondoffive 264, 287, 302, 384, 390, 406 \@sect 104, <u>106</u> \@setref 281 \@spart 136, 137 \@ssect 111, 112 \@tempa 72, 83, 91, 93, 94, 192, 193, 382, 396, 400, 413, 418, 419 \@tempb 388, 396, 400 \@tempcsta 419, 420, 422, 424, 425, 435, 436, 437 \@thirdoffive 265, 314, 326 \@undefined 278, 408 \@vpageref 461 \@writetocindents@ 89	121, 132, 137, 142, 149, 156, 173, 183, 190, 192, 202, 211, 218, 223, 238, 249, 254, 263, 264, 265, 266, 267, 270, 277, 283, 286, 292, 298, 311, 320, 345, 349, 354, 357, 358, 364, 377, 466, 469, 485 \descriptionlabel 201, 202 \do 91
		E
		\edef 8, 72, 222, 247, 250, 367, 372, 382, 388, 404
		\else 124, 155, 159, 162, 194, 291, 319, 363, 397, 410, 415, 428, 431, 434, 439, 442, 446, 487
		\endcsname 94, 219, 220, 223, 226, 275, 362, 366, 384, 390, 406
		\endgroup 21, 40, 58, 82, 98, 222, 252, 274, 315, 327, 372
		\expandafter 9, 82, 158, 163, 219, 223, 226, 250, 252, 273, 275, 383, 389, 394, 405, 456
		F
		\f 61, 84, 85, 126, 164, 165, 166, 196, 258, 280, 304, 305, 329, 330, 402, 412, 430, 433, 444, 445, 448, 449, 453, 463, 489
		G
		\getrefbykeydefault . .

<p>..... 357, 358</p> <p>\GetTitleString 101</p> <p>\GetTitleStringResult 102</p> <p>\global 19, 379</p>	<p>M</p> <p>\M@sect 120, 121</p> <p>\MakeUppercase ... 470</p> <p>\maxdimen 422</p> <p>\meaning 250</p>	<p>\NRorg@LT@c@ption 189, 191</p> <p>\NRorg@M@sect 120, 127</p> <p>\NRorg@opargbegintheorem</p> <p>..... 237, 240</p> <p>\NRorg@ttl@sect@i</p> <p>..... 210, 213</p>
	N	
	<p>\Nameref 345</p> <p>\nameref 337, 341, 345, 460</p> <p>\newcounter 105</p> <p>\newif 13</p> <p>\newlabel . 33, 51, 74, 93</p> <p>\nobreak 84</p> <p>\noexpand 71,</p> <p>..... 223, 225, 226, 399</p> <p>\NR@caption . 182, 185</p> <p>\NR@setref .. 275, 277</p> <p>\NR@@vpageref 370, 377</p>	<p>\NR@chapter 141, 144, 168</p> <p>\NR@gettitle 100, 108,</p> <p>..... 113, 123, 125,</p> <p>..... 133, 138, 143,</p> <p>..... 151, 154, 158,</p> <p>..... 161, 163, 174,</p> <p>..... 184, 195, 203,</p> <p>..... 212, 225, 239, 255</p>
	P	
	<p>\pageref ... 309, 345, 358</p> <p>\protect 71</p> <p>\protected@write . 32, 50</p> <p>\providecommand ..</p> <p>..... 23, 261,</p> <p>..... 262, 268, 269, 346</p>	
	R	
	<p>\Ref 476</p> <p>\ref 308, 357</p> <p>\reftextafter .. 429, 432</p> <p>\reftextbefore . 438, 443</p> <p>\reftextfaceafter 427</p> <p>\reftextfacebefore .. 441</p> <p>\reftextfaraway 447, 451</p> <p>\relax 70, 279, 362</p> <p>\RequirePackage . 2, 3, 4</p>	
	S	
	<p>\Sectionformat</p> <p>..... 109, 114, 346</p> <p>\setcounter 107</p> <p>\SK@ .. 46, 294, 300, 322</p> <p>\SK@label 46</p> <p>\SK@ref . 294, 300, 322</p> <p>\SK@ref 290, 318</p> <p>\slabel 63</p> <p>\space 400, 409</p> <p>\string 33, 51, 74, 93, 247</p>	
	T	
	<p>\T@nameref ... 311, 342</p> <p>\T@pageref 286, 298, 309</p> <p>\T@Ref 466, 477</p> <p>\T@ref 283, 292, 308</p> <p>\the 373, 380,</p> <p>..... 381, 384, 386,</p> <p>..... 387, 390, 394, 456</p>	
	U	
	<p>\thepage .. 35, 53, 70, 76</p> <p>\thesubequation 75</p> <p>\thevpagerefnum 404,</p> <p>..... 413, 417, 424, 436</p> <p>\toks@ 369, 373</p> <p>\ttl@sect@i ... 210, 211</p>	
	U	
	<p>\NRorg@lst@Make-</p> <p>Caption . 484, 490</p>	<p>\unskip ... 378, 460, 461</p>

	V		\vref@space	... 408, 411			368, 372, 373, 375
	\vnameref 459	W		\write 73, 92	Y
	\vref 399		X		\y 249, 250
	\vref@err 398		x 222, 230, 247, 248, 253, 367,		Z
						\z 250, 251, 253