

Warnings and errors for the expl3 analysis tool

Vít Starý Novotný

2025-04-25

Contents

Introduction	4
1 Preprocessing	4
No standard delimiters [W100]	4
Unexpected delimiters [W101]	5
Expl3 material in non-expl3 parts [E102]	5
Line too long [S103]	5
Multiple delimiters <code>\ProvidesExpl*</code> in a single file [E104]	6
2 Lexical analysis	6
“Do not use” argument specifiers [W200]	6
Unknown argument specifiers [E201]	6
Deprecated control sequences [W202]	7
Missing stylistic whitespaces [S204]	7
Malformed function name [S205]	7
Malformed variable or constant name [S206]	7
Malformed quark or scan mark name [S207]	8
Too many closing braces [E208]	8
Invalid characters [E209]	9
3 Syntactic analysis	9
Unexpected function call argument [E300]	9
End of expl3 part within function call [E301]	9
Unbraced n-type function call argument [W302]	10
Braced N-type function call argument [W303]	10
4 Unexpected parameter number	10
5 Semantic analysis	10
5.1 Functions and conditional functions	10
Expanding an unexpandable variable or constant [T500]	10
Unused function [W501]	11
Unused function variant [W502]	11

	Function variant of incompatible type [T503]	11
	Protected predicate function [E504]	12
	Function variant for an undefined conditional function [E505] . .	12
	Multiply defined function variant [W506]	12
	Calling an undefined function [E507]	13
	Calling an undefined function variant [E508]	13
5.2	Variables and constants	13
	Unused variable or constant [W509]	13
	Setting an undeclared variable [W510]	14
	Setting a constant [E511]	14
	Using a token list variable or constant without an accessor [W512]	14
	Using non-token-list variable or constant without an accessor [E513]	15
	Multiply declared variable or constant [E514]	15
	Using an undefined variable or constant [E515]	15
	Locally setting a global variable [E516]	16
	Globally setting a local variable [E517]	16
	Using a variable of an incompatible type [T518]	16
5.3	Messages	17
	Unused message [W519]	17
	Setting an undefined message [W520]	18
	Multiply defined message [E521]	18
	Using an undefined message [E522]	18
	Incorrect parameters in message text [E523]	18
5.4	Sorting	19
	Comparison conditional without signature :nnTF [E524]	19
6	Flow analysis	19
6.1	Functions and conditional functions	19
	Multiply defined function [E600]	19
	Unreachable function [W601]	20
	Unreachable function variant [W602]	21
	Calling a function before definition [E603]	21
	Calling a function variant before definition [E604]	21
	Setting a function before definition [W605]	22
	Unexpandable or restricted-expandable boolean expression [E606]	22
	Expanding an unexpandable function [E607]	23
	Fully-expanding a restricted-expandable function [E608]	23
	Defined an expandable function as protected [W609]	24
	Defined an unexpandable function as unprotected [W610]	24
	Conditional function with no return value [E611]	25
	Comparison code with no return value [E612]	25
6.2	Variables and constants	26
	Unreachable variable or constant [W613]	26
	Setting a variable before declaration [E614]	26
	Using a variable or constant before definition [E615]	26
6.3	Messages	27

	Unreachable message [W616]	27
	Setting a message before definition [E617]	27
	Using a message before definition [E618]	27
	Too few arguments supplied to message [E619]	28
6.4	Input-output streams	29
	Using an unopened or closed stream [E620]	29
	Multiply opened stream [E621]	29
	Unclosed stream [W622]	30
6.5	Piecewise token list construction	30
	Building on a regular token list [T623]	30
	Using a semi-built token list [T624]	31
	Multiply started building a token list [E625]	31
	Unfinished semi-built token list [W626]	31
	Caveats	32
	References	34
	Index	35

Introduction

In this document, I list the warnings and errors for the different processing steps of the expl3 linter [1]:

Preprocessing Determine which parts of the input files contain expl3 code.

Lexical analysis Convert expl3 parts of the input files into T_EX tokens.

Syntactic analysis Convert T_EX tokens into a tree of function calls.

Semantic analysis Determine the meaning of the different function calls.

Flow analysis Determine additional emergent properties of the code.

For each warning and error, I specify a unique identifier that can be used to disable the warning or error, a description of the condition for the warning or error, and a code example that demonstrates the condition and serves as a test case for the linter.

Warnings and errors have different types that decides the prefix of their identifiers:

- Warnings:
 - S : Style warnings
 - W : Other warnings
- Errors:
 - T : Type errors
 - E : Other errors

1 Preprocessing

In the preprocessing step, the expl3 analysis tool determines which parts of the input files contain expl3 code. Inline T_EX comments that disable warnings and errors are also analyzed in this step.

No standard delimiters [W100]

An input file contains no delimiters such as `\ExplSyntaxOn`, `\ExplSyntaxOff`, `\ProvidesExplPackage`, `\ProvidesExplClass`, and `\ProvidesExplFile` [2, Section 2.1]. The analysis tool should assume that the whole input file is in expl3.

```
1 % file-wide warning
2 \tl_new:N
3   \g_example_tl
4 \tl_gset:Nn
5   \g_example_tl
```

```

6   { Hello,~ }
7   \tl_gput_right:Nn
8     \g_example_tl
9     { world! }
10  \tl_use:N
11    \g_example_tl

```

Unexpected delimiters [W101]

An input file contains extraneous `\ExplSyntaxOn` delimiters [2, Section 2.1] in `expl3` parts or extraneous `\ExplSyntaxOff` delimiters in non-`expl3` parts.

```

1  \input expl3-generic
2  \ExplSyntaxOff % warning on this line
3  \ExplSyntaxOn
4  \tl_new:N
5    \g_example_tl
6  \tl_gset:Nn
7    \g_example_tl
8    { Hello,~ }
9  \ExplSyntaxOn % warning on this line
10 \tl_gput_right:Nn
11   \g_example_tl
12   { world! }
13 \tl_use:N
14   \g_example_tl

```

Expl3 material in non-expl3 parts [E102]

An input file contains what looks like `expl3` material [2, Section 1.1] in non-`expl3` parts.

```

1  \ProvidesExplFile{example.tex}{2024-04-09}{1.0.0}{An example
   ↪ file}
2  \tl_new:N
3    \g_example_tl
4  \tl_gset:Nn
5    \g_example_tl
6    { Hello,~ }
7  \tl_gput_right:Nn
8    \g_example_tl
9    { world! }
10 \ExplSyntaxOff
11 \tl_use:N % error on this line
12   \g_example_tl % error on this line

```

Line too long [S103]

Some lines in `expl3` parts are longer than 80 characters [3, Section 2].

```

1 This line is not very long, because it is 80 characters long, not
  ↪ 81 characters.
2 This line is overly long, because it is 81 characters long
  ↪ excluding the comment. % warning on this line
3 This line is not very long, because it is 80 characters long,
  ↪ comments excluded. % no warning on this line

```

The maximum line length can be configured using the command-line option `--max-line-length` or with the Lua option `max_line_length`.

Multiple delimiters `\ProvidesExpl*` in a single file [E104]

An input file contains multiple delimiters `\ProvidesExplPackage`, `\ProvidesExplClass`, and `\ProvidesExplFile`.

```

1 \ProvidesExplPackage
2   {example.sty}{2024-04-09}{1.0.0}{An example package}
3 \ExplSyntaxOff
4 \ProvidesExplClass % error on this line
5   {example.cls}{2024-04-09}{1.0.0}{An example class}

```

2 Lexical analysis

In the lexical analysis step, the `expl3` analysis tool converts the `expl3` parts of the input files into a list of `TEX` tokens.

“Do not use” argument specifiers [W200]

Some control sequence tokens correspond to functions with `D` (do not use) argument specifiers.

```

1 \tex_space:D % warning on this line
2 \tex_italiccor^^3aD % warning on this line
3 \tex_hyphen^^zD % warning on this line
4 \tex_let:^^44 % warning on this line

```

The above example has been taken from The L^AT_EX Project [2, Chapter 24].

Unknown argument specifiers [E201]

Some control sequence tokens correspond to functions with unknown argument specifiers. [2, Section 1.1]

```

1 \cs_new:Nn
2   \example:bar % error on this line
3   { foo }
4   { bar }
5   { baz }

```

Deprecated control sequences [W202]

Some control sequence tokens correspond to deprecated expl3 control sequences from `l3obsolete.txt` [5].

```
1 \str_lower_case:n % warning on this line
2 { FOO BAR }
```

Missing stylistic whitespaces [S204]

Some control sequences and curly braces are not surrounded by whitespaces [4, Section 6, 3, Section 3].

```
1 \cs_new:Npn \foo_bar:Nn #1#2
2 {
3   \cs_if_exist:NTF#1 % warning on this line
4     { \__foo_bar:n {#2} }
5     { \__foo_bar:nn{#2}{literal} } % warning on this line
6 }
```

Malformed function name [S205]

Some function have names that are not in the format `\⟨module⟩_⟨description⟩:⟨arg-spec⟩` [4, Section 3.2].

```
1 \cs_new:Nn
2   \description: % warning on this line
3   { foo }

1 \cs_gset:Npn
2   \module__description: % warning on this line
3   { foo }

1 \cs_set_eq:Nn
2   \module_description: % warning on this line
3   { foo }

1 \cs_generate_from_arg_count:NNnn
2   \__module_description:
3   \cs_new:Npn
4   { 0 }
5   { foo }
```

Malformed variable or constant name [S206]

Some expl3 variables and constants have names that are not in the format `\⟨scope⟩_⟨module⟩_⟨description⟩_⟨type⟩` [4, Section 3.2], where the `⟨module⟩` part is optional.

```
1 \tl_new:N
2   \g_description_tl % warning on this line
```

```

3 \box_new:N
4   \l__description_box % warning on this line
5 \int_const:Nn
6   \c_description % warning on this line
7   { 123 }

1 \regex_new:N
2   \g_module_description_regex
3 \coffin_new:N
4   \l_module_description_coffin
5 \str_const:Nn
6   \c__module_description_str
7   { foo }

```

An exception is made for scratch variables [2, Section 1.1.1]:

```

1 \tl_use:N
2   \l_tmpa_tl
3 \int_gset:Nn
4   \g_tmpb_int
5   { 1 + 2 }
6 \str_show:N
7   \g_tmpa_str
8 \bool_set_true:N
9   \l_tmpa_bool

```

Malformed quark or scan mark name [S207]

Some expl3 quarks and scan marks have names that do not start with `\q_` and `\s_`, respectively [4, Chapter 19].

```

1 \quark_new:N
2   \foo_bar % error on this line

1 \quark_new:N
2   \q_foo_bar

1 \scan_new:N
2   \foo_bar % error on this line

1 \scan_new:N
2   \s_foo_bar

```

Too many closing braces [E208]

An expl3 part of the input file contains too many closing braces.

```

1 \tl_new:N
2   \g_example_tl
3 \tl_gset:Nn
4   \g_example_tl
5   { Hello,~ } } % error on this line

```


Invalid characters [E209]

An expl3 part of the input file contains invalid characters.

```
1 ^^7f % error on this line
2 \fo^^?o % error on this line
```

3 Syntactic analysis

In the syntactic analysis step, the expl3 analysis tool converts the list of T_EX tokens into a tree of function calls.

Unexpected function call argument [E300]

A function is called with an unexpected argument.

```
1 \cs_new:Nn
2   { unexpected } % error on this line
3   \l_tmpa_tl
4
5 {
6   \cs_new:Npn
7     \example_foo:w
8     #1 } % error on this line
9   { foo~#1 }
```

Partial applications are detected by analysing closing braces (}) and do not produce an error:

```
1 \cs_new:Nn
2   \example_foo:n
3   { foo~#1 }
4 \cs_new:Nn
5   \example_bar:
6   { \example_foo:n }
7 \cs_new:Nn
8   \example_baz:
9   {
10     \example_bar:
11     { bar }
12 }
```

End of expl3 part within function call [E301]

A function call is cut off by the end of a file or an expl3 part of a file:

```
1 \cs_new:Nn % error on this line
2   \example_foo:n
```

Unbraced n-type function call argument [W302]

An n-type function call argument is unbraced:

```
1 \tl_set:No
2   \l_tmpa_tl
3   \l_tmpb_tl % error on this line
```

Depending on the specific function, this may or may not be an error.

Braced N-type function call argument [W303]

An N-type function call argument is braced:

```
1 \cs_new:Nn
2   { \example_foo:n } % warning on this line
3   { bar }
```

Depending on the specific function, this may or may not be an error.

4 Unexpected parameter number

A parameter or replacement text contains parameter tokens (#) followed by unexpected numbers:

```
1 \cs_new:Npn
2   \example_foo:nnn
3   #1#2#9 % error on this line
4   { foo~#1 }

1 \cs_new:Npn
2   \example_foo:nnn
3   #1#2#3
4   { foo~#4 } % error on this line
```

5 Semantic analysis

In the semantic analysis step, the expl3 analysis tool determines the meaning of the different function calls.

5.1 Functions and conditional functions

Expanding an unexpandable variable or constant [T500]

A function with a V-type argument is called with a variable or constant that does not support V-type expansion [2, Section 1.1].

```
1 \cs_new:Nn
2   \module_foo:n
3   { #1 }
```

```

4 \cs_generate_variant:Nn
5   \module_foo:n
6   { V }
7 \module_foo:V % error on this line
8   \c_false_bool

```

Unused function [W501]

A private function or conditional function is defined but unused.

```

1 \cs_new:Nn % warning on this line
2   \__module_foo:
3   { bar }

1 \prg_new_conditional:Nnn % warning on this line
2   \__module_foo:
3   { p, T, F, TF }
4   { \prg_return_true: }

```

Unused function variant [W502]

A private function or conditional function variant is defined but unused.

```

1 \cs_new:Nn
2   \__module_foo:n
3   { bar~#1 }
4 \cs_generate_variant:Nn % warning on this line
5   \__module_foo:n
6   { V }
7 \__module_foo:n
8   { baz }

1 \prg_new_conditional:Nnn
2   \__module_foo:n
3   { p, T, F, TF }
4   { \prg_return_true: }
5 \prg_generate_conditional_variant:Nnn % warning on this line
6   \__module_foo:n
7   { TF }
8   { V }
9 \__module_foo:nTF
10  { foo }
11  { bar }
12  { baz }

```

Function variant of incompatible type [T503]

A function variant is generated from an incompatible argument type [2, Section 5.2, documentation of function `\cs_generate_variant:Nn`].

```

1 \cs_new:Nn

```

```

2   \module_foo:Nn
3   { bar }
4   \cs_generate_variant:Nn % error on this line
5   \module_foo:Nn
6   { nn }
7   \cs_generate_variant:Nn % error on this line
8   \module_foo:Nn
9   { NN }

```

Protected predicate function [E504]

A protected predicate function is defined.

```

1   \prg_new_protected_conditional:Nnn
2   \module_foo:
3   { p }
4   { \prg_return_true: }

```

Function variant for an undefined conditional function [E505]

A variant is defined for an undefined conditional function.

```

1   \prg_new_conditional:Nnn
2   \module_foo:n
3   { p, T, F }
4   { \prg_return_true: }
5   \prg_generate_conditional_variant:Nnn % warning on this line
6   \module_foo:n
7   { TF }
8   { V }
9   \module_foo:nT
10  { bar }
11  { baz }

```

Multiply defined function variant [W506]

A function or conditional function is defined multiple times.

```

1   \cs_new:Nn
2   \module_foo:n
3   { bar~#1 }
4   \cs_generate_variant:Nn
5   \module_foo:n
6   { V }
7   \cs_generate_variant:Nn % warning on this line
8   \module_foo:n
9   { o, V }

1   \prg_new_conditional:Nnn
2   \module_foo:n

```

```

3   { p, T, F, TF }
4   { \prg_return_true: }
5   \prg_generate_conditional_variant:Nnn
6   \module_foo:n
7   { TF }
8   { V }
9   \prg_generate_conditional_variant:Nnn % warning on this line
10  \module_foo:n
11  { TF }
12  { o, V }

```

Calling an undefined function [E507]

A function is used but undefined.

```

1  \module_foo: % error on this line

```

Calling an undefined function variant [E508]

A function or conditional function variant is used but undefined.

```

1  \cs_new:Nn
2  \module_foo:n
3  { bar~#1 }
4  \tl_set:Nn
5  \l_tmpa_tl
6  { baz }
7  \module_foo:V % error on this line
8  \l_tmpa_tl

1  \prg_new_conditional:Nnn
2  \module_foo:n
3  { p, T, F, TF }
4  { \prg_return_true: }
5  \prg_generate_conditional_variant:Nnn
6  \module_foo:n
7  { TF }
8  { V }
9  \module_foo:VTF % error on this line
10 \l_tmpa_tl
11 { foo }
12 { bar }

```

5.2 Variables and constants

Unused variable or constant [W509]

A variable or a constant is declared and perhaps defined but unused.

```

1  \tl_new:N % warning on this line
2  \g_declared_but_undefined_tl

```

```

1 \tl_new:N % warning on this line
2   \g_defined_but_unused_tl
3 \tl_gset:Nn
4   \g_defined_but_unused_tl
5   { foo }

1 \tl_new:N
2   \g_defined_but_unused_tl
3 \tl_gset:Nn
4   \g_defined_but_unused_tl
5   { foo }
6 \tl_use:N
7   \g_defined_but_unused_tl

1 \tl_const:Nn % warning on this line
2   \c_defined_but_unused_tl
3   { foo }

1 \tl_const:Nn
2   \c_defined_but_unused_tl
3   { foo }
4 \tl_use:N
5   \c_defined_but_unused_tl

```

Setting an undeclared variable [W510]

An undeclared variable is set.

```

1 \tl_gset:Nn % warning on this line
2   \g_example_tl
3   { bar }

```

Setting a constant [E511]

A constant is set.

```

1 \tl_gset:Nn % error on this line
2   \c_example_tl
3   { bar }

```

Using a token list variable or constant without an accessor [W512]

A token list variable or constant is used without an accessor function.

```

1 \tl_set:Nn
2   \l_tmpa_tl
3   { world }
4 Hello,~\l_tmpa_tl! % warning on this line
5 Hello,~\tl_use:N \l_tmpa_tl !

```

This also applies to subtypes of token lists such as strings and comma-lists:

```

1  \str_set:Nn
2    \l_tmpa_str
3    { world }
4  Hello,~\l_tmpa_str!  % warning on this line
5  Hello,~\str_use:N \l_tmpa_str !

1  \clist_set:Nn
2    \l_tmpa_clist
3    { world }
4  Hello,~\l_tmpa_clist!  % warning on this line
5  Hello,~\clist_use:Nn \l_tmpa_clist { and } !

```

Using non-token-list variable or constant without an accessor [E513]

A non-token-list variable or constant is used without an accessor function.

```

1  Hello,~\l_tmpa_seq!  % error on this line
2  Hello,~\seq_use:Nn \l_tmpa_seq { and } !

```

Note that boolean and integer variables may be used without accessor functions in boolean and integer expressions, respectively. Therefore, we may want to initially exclude them from this check to prevent false positives.

Multiply declared variable or constant [E514]

A variable or constant is declared multiple times.

```

1  \tl_new:N
2    \g_example_tl
3  \tl_new:N  % error on this line
4    \g_example_tl

1  \tl_const:Nn
2    \c_example_tl
3    { foo }
4  \tl_const:Nn  % error on this line
5    \c_example_tl
6    { bar }

```

Using an undefined variable or constant [E515]

A variable or constant is used but undeclared or undefined.

```

1  \tl_use:N  % error on this line
2    \g_undeclared_tl

1  \tl_new:N
2    \g_declared_but_undefined_tl
3  \tl_use:N  % error on this line
4    \g_declared_but_undefined_tl

```

```

1 \tl_new:N
2   \g_defined_tl
3 \tl_gset:Nn
4   \g_defined_tl
5   { foo }
6 \tl_use:N
7   \g_defined_tl

1 \tl_use:N % error on this line
2   \c_undefined_tl

1 \tl_const:Nn
2   \c_defined_tl
3   { foo }
4 \tl_use:N
5   \c_defined_tl

```

Locally setting a global variable [E516]

A global variable is locally set.

```

1 \tl_new:N
2   \g_example_tl
3 \tl_set:Nn % error on this line
4   \g_example_tl
5   { foo }

```

Globally setting a local variable [E517]

A local variable is globally set.

```

1 \tl_new:N
2   \l_example_tl
3 \tl_gset:Nn % error on this line
4   \l_example_tl
5   { foo }

```

Using a variable of an incompatible type [T518]

A variable of one type is used where a variable of a different type should be used.

```

1 \tl_new:N
2   \l_example_str % error on this line

1 \ior_new:N
2   \l_example_ior
3 \iow_open:Nn
4   \l_example_ior % error on this line
5   { example }

```



```

1 \clist_new:N
2   \l_example_clist
3 \tl_set:Nn
4   \l_tmpa_tl
5   { foo }
6 \clist_set_eq:NN
7   \l_example_clist
8   \l_tmpa_tl % error on this line

1 \tl_set:Nn
2   \l_tmpa_tl
3   { foo }
4 \seq_set_from_clist:NN
5   \l_tmpa_seq
6   \l_tmpa_tl % error on this line

1 \tl_set:Nn
2   \l_tmpa_tl
3   { foo }
4 \regex_set:Nn
5   \l_tmpa_regex
6   { foo }
7 \int_set:Nn
8   \l_tmpa_int
9   { 1 + 2 }
10 \regex_show:N
11   \l_tmpa_tl
12 \regex_show:N
13   \l_tmpa_regex
14 \regex_show:N
15   \l_tmpa_int % error on this line

1 \tl_set:Nn
2   \l_tmpa_tl
3   { foo }
4 \int_set_eq:NN
5   \l_tmpa_int
6   \l_tmpa_tl % error on this line

```

5.3 Messages

Unused message [W519]

A message is defined but unused.

```

1 \msg_new:nnn % warning on this line
2   { foo }
3   { bar }
4   { baz }

```

```

1  \msg_new:nnn
2    { bar }
3    { bar }
4    { baz }
5  \msg_info:nn
6    { bar }
7    { bar }

```

Setting an undefined message [W520]

A message is set but undefined.

```

1  \msg_set:nnn % error on this line
2    { foo }
3    { bar }
4    { baz }

1  \msg_new:nnn
2    { foo }
3    { bar }
4    { baz }
5  \msg_set:nnn
6    { foo }
7    { bar }
8    { baz }

```

Multiply defined message [E521]

A message is defined multiple times.

```

1  \msg_new:nnn
2    { foo }
3    { bar }
4    { baz }
5  \msg_new:nnn % error on this line
6    { foo }
7    { bar }
8    { baz }

```

Using an undefined message [E522]

A message is used but undefined.

```

1  \msg_info:nn
2    { foo }
3    { bar }

```

Incorrect parameters in message text [E523]

Parameter tokens other than #1, #2, #3, and #4 are specified in a message text.

```

1  \msg_new:nnn
2    { foo }
3    { bar }
4    { #5 } % error on this line

1  \msg_new:nnnn
2    { foo }
3    { bar }
4    { #4 }
5    { #5 } % error on this line

```

5.4 Sorting

Comparison conditional without signature :nnTF [E524]

A sorting function is called with a conditional that has a signature different than :nnTF [2, Section 15.5.4].

```

1  \cs_new:Nn
2    \example_foo:
3    { \prg_return_true: }
4  \tl_sort:nN
5    { { foo } { bar } }
6    \example_foo:TF

```

6 Flow analysis

In the flow analysis step, the expl3 analysis tool determines compiler-theoretic properties of functions, such as expandability, and variables, such as reaching definitions.

6.1 Functions and conditional functions

Multiply defined function [E600]

A function or conditional function is defined multiple times.

```

1  \cs_new:Nn
2    \module_foo:
3    { bar }
4  \cs_new:Nn % error on this line
5    \module_foo:
6    { bar }

1  \cs_new:Nn
2    \module_foo:
3    { bar }
4  \cs_undefine:N

```

```

5     \module_foo:
6 \cs_new:Nn
7     \module_foo:
8     { bar }

1  \prg_new_conditional:Nnn
2     \module_foo:
3     { p, T, F, TF }
4     { \prg_return_true: }
5 \prg_new_conditional:Nnn % error on this line
6     \module_foo:
7     { p, T, F, TF }
8     { \prg_return_true: }

1  \prg_new_conditional:Nnn
2     \module_foo:
3     { p, T, F, TF }
4     { \prg_return_true: }
5 \cs_undefine:N
6     \module_foo_p:
7 \cs_undefine:N
8     \module_foo:T
9 \cs_undefine:N
10    \module_foo:F
11 \cs_undefine:N
12    \module_foo:TF
13 \prg_new_conditional:Nnn
14    \module_foo:
15    { p, T, F, TF }
16    { \prg_return_true: }

```

Unreachable function [W601]

A private function or conditional function is defined but all its calls are unreachable.¹

```

1 \cs_new:Nn % warning on this line
2     \__module_foo:
3     { bar }
4 \cs_new:Nn
5     \__module_baz:
6     { \__module_foo: }

```

This check is a stronger version of W501 and should only be emitted if W501 has not previously been emitted for this function.

¹Code is unreachable if it is only reachable through private functions which that are either unused or also unreachable.

Unreachable function variant [W602]

A private function or conditional function variant is defined but all its calls are unreachable.

```
1 \cs_new:Nn
2   \__module_foo:n
3   { bar~#1 }
4 \cs_new:Nn
5   \__module_baz:
6   {
7     \tl_set:Nn
8       \l_tmpa_tl
9       { baz }
10    \__module_foo:V
11    \l_tmpa_tl
12  }
13 \cs_generate_variant:Nn % warning on this line
14   \__module_foo:n
15   { V }
16 \__module_foo:n
17 { baz }
```

This check is a stronger version of W502 and should only be emitted if W502 has not previously been emitted for this function variant.

Calling a function before definition [E603]

A function is used before it has been defined or after it has been undefined.

```
1 \module_foo: % error on this line
2 \cs_new:Nn
3   \module_foo:
4   { bar }

1 \cs_new:Nn
2   \module_foo:
3   { bar }
4 \cs_undefine:N
5   \module_foo:
6 \module_foo: % error on this line
```

This check is a stronger version of E507 and should only be emitted if E507 has not previously been emitted for this function.

Calling a function variant before definition [E604]

A function or conditional function variant is used before it has been defined.

```
1 \cs_new:Nn
2   \module_foo:n
```

```

3     { bar~#1 }
4 \tl_set:Nn
5   \l_tmpa_tl
6   { baz }
7 \module_foo:V % error on this line
8   \l_tmpa_tl
9 \cs_generate_variant:Nn
10  \module_foo:n
11  { V }

```

This check is a stronger version of E508 and should only be emitted if E508 has not previously been emitted for this function variant.

Setting a function before definition [W605]

A function is set before it has been defined or after it has been undefined.

```

1 \cs_gset:N % warning on this line
2   \module_foo:
3   { foo }
4 \cs_new:Nn
5   \module_foo:
6   { bar }

1 \cs_new:Nn
2   \module_foo:
3   { bar }
4 \cs_undefine:N
5   \module_foo:
6 \cs_gset:N % warning on this line
7   \module_foo:
8   { foo }

```

Unexpandable or restricted-expandable boolean expression [E606]

A boolean expression [2, Section 9.2] is not fully-expandable.

```

1 \cs_new_protected:N
2   \example_unexpandable:
3   {
4     \tl_set:Nn
5       \l_tmpa_tl
6       { bar }
7     \c_true_bool
8   }
9 \cs_new:N
10  \example_restricted_expandable:
11  {
12    \bool_do_while:Nn

```

```

13         \c_false_bool
14         { }
15         \c_true_bool
16     }
17 \cs_new_protected:N
18     \example_expandable:
19     { \c_true_bool }
20 \bool_set:Nn
21     \l_tmpa_bool
22     { \example_unexpandable: } % error on this line
23 \bool_set:Nn
24     \l_tmpa_bool
25     { \example_restricted_expandable: } % error on this line
26 \bool_set:Nn
27     \l_tmpa_bool
28     { \example_expandable: }

```

Expanding an unexpandable function [E607]

An unexpandable function or conditional function is called within an x-type, e-type, or f-type argument.

```

1 \cs_new_protected:N
2     \example_unexpandable:
3     {
4         \tl_set:Nn
5             \l_tmpa_tl
6             { bar }
7     }
8 \cs_new:N
9     \module_foo:n
10    { #1 }
11 \cs_generate_variant:Nn
12     \module_foo:n
13     { x, e, f }
14 \module_foo:n
15     { \example_unexpandable: }
16 \module_foo:x
17     { \example_unexpandable: } % error on this line
18 \module_foo:e
19     { \example_unexpandable: } % error on this line
20 \module_foo:f
21     { \example_unexpandable: } % error on this line

```

Fully-expanding a restricted-expandable function [E608]

An restricted-expandable function or conditional function is called within an f-type argument.

```

1  \cs_new:N
2    \example_restricted_expandable:
3    {
4      \int_to_roman:n
5        { 1 + 2 }
6    }
7  \cs_new:N
8    \module_foo:n
9    { #1 }
10 \cs_generate_variant:Nn
11   \module_foo:n
12   { x, e, f }
13 \module_foo:n
14   { \example_restricted_expandable: }
15 \module_foo:x
16   { \example_restricted_expandable: }
17 \module_foo:e
18   { \example_restricted_expandable: }
19 \module_foo:f
20   { \example_restricted_expandable: } % error on this line

```

Defined an expandable function as protected [W609]

A fully expandable function or conditional function is defined using a creator function `\cs_new_protected:*` or `\prg_new_protected_conditional:*`. [3, Section 4]

```

1  \cs_new_protected:Nn % warning on this line
2    \example_expandable:
3    { foo }

1  \prg_new_protected_conditional:Nnn % warning on this line
2    \example_expandable:
3    { T, F, TF }
4    { \prg_return_true: }

```

Defined an unexpandable function as unprotected [W610]

An unexpandable or restricted-expandable function or conditional function is defined using a creator function `\cs_new:*` or `\prg_new_conditional:*`. [3, Section 4]

```

1  \cs_new:Nn % warning on this line
2    \example_unexpandable:
3    {
4      \tl_set:Nn
5        \l_tmpa_tl
6        { bar }
7    }

```



```

1 \prg_new_conditional:Nnn % warning on this line
2   \example_unexpandable:
3   { p, T, F, TF }
4   {
5     \tl_set:Nn
6       \l_tmpa_tl
7       { bar }
8     \prg_return_true:
9   }

```

Conditional function with no return value [E611]

A conditional functions has no return value.

```

1 \prg_new_conditional:Nnn % error on this line
2   \example_no_return_value:
3   { p, T, F, TF }
4   { foo }

1 \prg_new_conditional:Nnn
2   \example_has_return_value:
3   { p, T, F, TF }
4   { \example_foo: }
5 \cs_new:Nn
6   \example_foo:
7   { \prg_return_true: }

```

Comparison code with no return value [E612]

A comparison code [2, Section 6.1] has no return value.

```

1 \clist_set:Nn
2   \l_foo_clist
3   { 3 , 01 , -2 , 5 , +1 }
4 \clist_sort:Nn % error on this line
5   \l_foo_clist
6   { foo }

1 \clist_set:Nn
2   \l_foo_clist
3   { 3 , 01 , -2 , 5 , +1 }
4 \clist_sort:Nn
5   \l_foo_clist
6   { \example_foo: }
7 \cs_new:Nn
8   \example_foo:
9   {
10     \int_compare:nNnTF { #1 } > { #2 }
11     { \sort_return_swapped: }

```

```

12     { \sort_return_same: }
13 }

```

The above example has been taken from The L^AT_EX Project [2, Chapter 6].

6.2 Variables and constants

Unreachable variable or constant [W613]

A variable or a constant is declared and perhaps defined but all its uses are unreachable.

```

1  \tl_new:N % warning on this line
2  \g_defined_but_unreachable_tl
3  \tl_gset:Nn
4  \g_defined_but_unreachable_tl
5  { foo }
6  \cs_new:Nn
7  \__module_baz:
8  {
9      \tl_use:N
10     \g_defined_but_unreachable_tl
11 }

```

This check is a stronger version of W509 and should only be emitted if W509 has not previously been emitted for this variable or constant.

Setting a variable before declaration [E614]

A variable is set before it has been declared.

```

1  \tl_gset:Nn % error on this line
2  \g_example_tl
3  { bar }
4  \tl_new:N
5  \g_example_tl

```

This check is a stronger version of W510 and should prevent W510 from being emitted for this variable.

Using a variable or constant before definition [E615]

A variable or constant is used before it has been defined.

```

1  \tl_new:N
2  \g_example_tl
3  \tl_use:N % error on this line
4  \g_example_tl
5  \tl_gset:Nn
6  \g_example_tl
7  { foo }

```

This check is a stronger version of E515 and should only be emitted if E515 has not previously been emitted for this variable or constant.

6.3 Messages

Unreachable message [W616]

A message is defined but all its uses are unreachable.

```
1  \msg_new:nnn % warning on this line
2    { foo }
3    { bar }
4    { baz }
5  \cs_new:Nn
6    \__module_baz:
7    {
8      \msg_info:nn
9        { foo }
10       { bar }
11    }
```

This check is a stronger version of W519 and should only be emitted if W519 has not previously been emitted for this message.

Setting a message before definition [E617]

A message is set before it has been defined.

```
1  \msg_set:nnn % error on this line
2    { foo }
3    { bar }
4    { baz }
5  \msg_new:nnn
6    { foo }
7    { bar }
8    { baz }
```

This check is a stronger version of W520 and should prevent W520 from being emitted for this message.

Using a message before definition [E618]

A message is used before it has been defined.

```
1  \msg_info:nn % error on this line
2    { foo }
3    { bar }
4  \msg_new:nnn
5    { foo }
6    { bar }
7    { baz }
```

This check is a stronger version of E522 and should only be emitted if E522 has not previously been emitted for this message.

Too few arguments supplied to message [E619]

A message was supplied fewer arguments than there are parameters in the message text.

```
1  \msg_new:nnn
2    { foo }
3    { bar }
4    { #1~#2 }
5  \msg_info:nn  % error on this line
6    { foo }
7    { bar }
8  \msg_info:nnn  % error on this line
9    { foo }
10   { bar }
11   { baz }
12  \msg_info:nnnn
13   { foo }
14   { bar }
15   { baz }
16   { baz }
```

Since a message can be redefined, we need to track the (possibly many) definitions that can be active when we display a message.

```
1  \msg_new:nnn
2    { foo }
3    { bar }
4    { #1 }
5  \msg_set:nnn
6    { foo }
7    { bar }
8    { baz }
9  \msg_info:nnn  % error on this line
10   { foo }
11   { bar }
12   { baz }

1  \msg_new:nnn
2    { foo }
3    { bar }
4    { #1 }
5  \msg_info:nnn
6    { foo }
7    { bar }
```

```

8     { baz }
9 \msg_set:nnn
10    { foo }
11    { bar }
12    { baz }

```

6.4 Input–output streams

Using an unopened or closed stream [E620]

A stream is used before it has been opened or after it has been closed.

```

1 \ior_new:N
2   \l_example_ior
3 \ior_str_get:NN % error on this line
4   \l_example_ior
5   \l_tmpa_tl
6 \ior_open:Nn
7   \l_example_ior
8   { example }

1 \ior_new:N
2   \l_example_ior
3 \ior_open:Nn
4   \l_example_ior
5   { example }
6 \ior_close:N
7   \l_example_ior
8 \ior_str_get:NN % error on this line
9   \l_example_ior
10  \l_tmpa_tl

```

Multiply opened stream [E621]

A stream is opened a second time without closing the stream first.

```

1 \iow_new:N
2   \l_example_iow
3 \iow_open:Nn
4   \l_example_iow
5   { foo }
6 \iow_open:Nn % error on this line
7   \l_example_iow
8   { bar }
9 \iow_close:N
10  \l_example_iow

```

Unclosed stream [W622]

A stream is opened but not closed.

```
1 % file-wide warning
2 \ior_new:N
3   \l_example_ior
4 \ior_open:Nn
5   \l_example_ior
6   { example }
```

6.5 Piecewise token list construction

Building on a regular token list [T623]

A token list variable is used with `\tl_build_*` functions before a function `\tl_build_*begin:N` has been called or after a function `\tl_build_*end:N` has been called.

```
1 \tl_new:N
2   \l_example_tl
3 \tl_build_put_right:Nn % error on this line
4   \l_example_tl
5   { foo }
6 \tl_build_begin:N
7   \l_example_tl
8 \tl_build_end:N
9   \l_example_tl
```

```
1 \tl_new:N
2   \l_example_tl
3 \tl_build_begin:N
4   \l_example_tl
5 \tl_build_put_right:Nn
6   \l_example_tl
7   { foo }
8 \tl_build_end:N
9   \l_example_tl
```

```
1 \tl_new:N
2   \l_example_tl
3 \tl_build_begin:N
4   \l_example_tl
5 \tl_build_end:N
6   \l_example_tl
7 \tl_build_put_right:Nn % error on this line
8   \l_example_tl
9   { foo }
```

Using a semi-built token list [T624]

A token list variable is used where a regular token list is expected after a function `\tl_build_*begin:N` has been called and before a function `\tl_build_*end:N` has been called.

```
1 \tl_new:N
2   \l_example_tl
3 \tl_use:N
4   \l_example_tl
5 \tl_build_begin:N
6   \l_example_tl
7 \tl_build_end:N
8   \l_example_tl

1 \tl_new:N
2   \l_example_tl
3 \tl_build_begin:N
4   \l_example_tl
5 \tl_use:N
6   \l_example_tl % error on this line
7 \tl_build_end:N
8   \l_example_tl

1 \tl_new:N
2   \l_example_tl
3 \tl_build_begin:N
4   \l_example_tl
5 \tl_build_end:N
6   \l_example_tl
7 \tl_use:N
8   \l_example_tl
```

Multiply started building a token list [E625]

A function `\tl_build_*begin:N` is called on a token list variable a second time without calling a function `\tl_build_*end:N` first.

```
1 \tl_new:N
2   \l_example_tl
3 \tl_build_begin:N
4   \l_example_tl
5 \tl_build_begin:N % error on this line
6   \l_example_tl
7 \tl_build_end:N
8   \l_example_tl
```

Unfinished semi-built token list [W626]

A function `\tl_build_*begin:N` is called on a token list variable without

calling a function `\tl_build_*end:N` later.

```

1 % file-wide warning
2 \tl_new:N
3   \l_example_tl
4 \tl_build_begin:N
5   \l_example_tl

```

Caveats

The warnings and errors in this documents do not cover the complete expl3 language. The caveats currently include the following areas, among others:

- Functions with “weird” (`w`) argument specifiers
- Verifying the `nopar` restriction on functions [2, Section 4.3.1]
- Symbolic evaluation of expansion functions [2, sections 5.4–5.10]
- Validation of parameters in (inline) functions (c.f. E523 and E619)
- Shorthands such as `\~` and `\\` in message texts [2, sections 11.4 and 12.1.3]
- Quotes in shell commands and file names [2, Section 10.7 and Chapter 12]
- Functions used outside their intended context:
 - `\sort_return_*`: outside comparison code [2, Section 6.1]
 - `\prg_return_*`: outside conditional functions [2, Section 9.1]
 - Predicates (`*_p:*`) outside boolean expressions [2, Section 9.3]
 - `*_map_break:*` outside a corresponding mapping [2, sections 9.8]
 - `\msg_line_*`, `\iow_char:N`, and `\iow_newline:` outside message text [2, sections 11.3 and 12.1.3]
 - `\iow_wrap_allow_break:` and `\iow_indent:n` outside wrapped message text [2, Section 12.1.4]
 - Boolean variable without an accessor function `\bool_to_str:N` outside boolean expressions [2, Section 21.4] (see E513)
 - Integer variable without an accessor function `\int_use:N` outside integer or floating point expressions [2, Section 21.4] (see E513)
 - Dimension variable without an accessor function `\dim_use:N` outside dimension or floating point expressions [2, Section 26.7] (see E513)
 - Skip variable without an accessor function `\skip_use:N` outside skip or floating point expressions [2, Section 26.14] (see E513)
 - Muskip variable without an accessor function `\muskip_use:N` outside muskip or floating point expressions [2, Section 26.21] (see E513)
 - Floating point variable without an accessor function `\fp_use:N` outside floating point expressions [2, Section 29.3] (see E513)
 - Box variable without accessor functions `\box_use(_drop)?:N` or `\[hv]box_unpack(_drop)?:N`, or without a measuring function `\box_(dp|ht|wd|ht_plus_dp):*` outside dimension or floating point expressions [2, sections 35.2 and 35.3]
 - Coffin variable without accessor function `\coffin_typeset:Nnnnn` outside dimension or floating point expressions [2, Section 36.4]

- Validation of literal expressions:
 - Comparison expressions in functions `*_compare(_p:n|:nT?F?)`
 - Regular expressions and replacement text [2, sections 8.1 and 8.2]
 - Boolean expressions [2, Section 9.3]
 - Integer expressions and bases [2, sections 21.1 and 21.8]
 - Dimension, skip, and muskip expressions [2, Chapter 26]
 - Floating point expressions [2, Section 29.12]
 - Color expressions [2, Chapter 37.3]
- Validation of naming schemes and member access:
 - String encoding and escaping [2, Section 18.1]
 - Key–value interfaces [2, Chapter 27]:
 - * Are keys defined at the point of use or is the module or its subdivision set up to accept unknown keys? [2, sections 27.2, 27.5, and 27.6]
 - * Are inheritance parents, choices, multi-choices, and groups used in a key definition defined at points of use? [2, sections 27.1, 27.3, and 27.7]
 - Floating-point symbolic expressions and user-defined functions [2, sections 29.6 and 29.7]
 - Names of bitset indexes [2, Section 31.1]
 - BCP-47 language tags [2, Section 34.2]
 - Color support [2, Chapter 37]:
 - * Named colors [2, Section 37.4]
 - * Color export targets [2, Section 37.8]
 - * Color models and their families and params [2, sections 37.2 and 37.9]
- Function `\file_input_stop`: not used on its own line [2, Section 12.2.3]
- Exhaustively or fully expanding quarks and scan marks [2, Chapter 19]
- Bounds checking for accessing constant sequences and other sequences where the number of items can be easily bounded such as integer and floating point arrays [2, chapters 28 and 30]:
 - Index checking functions `*_range*:*` and `*_item*:*`
 - Endless loop checking in functions `*_step*:*` [2, Section 21.7]
 - Number of symbols in a value-to-symbol mapping [2, Section 21.8]
- Applying functions `\clist_remove_duplicates:N` and `\clist_if_in:*` to comma lists that contain `{`, `}`, or `*` [2, sections 23.3 and 23.4]
- Incorrect parameters to function `\char_generate:nn` [2, Section 24.1]
- Incorrect parameters to functions `\char_set_*code:nn` [2, Section 24.2]
- Using implicit tokens `\c_catcode_(letter|other)_token` or the token list `\c_catcode_active_tl` [2, Section 24.3]

- Validation of key–value interfaces [2, Chapter 27]:
 - Setting a key with some properties `.*_g?(set|put)*:*` should be validated similarly to calling the corresponding functions directly: Have the variables been declared, do they have the correct type, does the value have the correct type?
 - Do points of use always set keys with property `.value_required:n` and never set keys with property `.value_forbidden:n`?
- Horizontal box operation on a vertical box or vice versa [2, Chapter 35]

References

- [1] Vít Starý Novotný. *Static analysis of expl3 programs (3). Design Specification*. To be released. URL: <https://witiko.github.io/Expl3-Linter-3/>.
- [2] The L^AT_EX Project. *The L^AT_EX3 interfaces*. The referenced version of the document is attached to this document. May 8, 2024. URL: <http://mirrors.ctan.org/macros/latex/required/l3kernel/interface3.pdf> (visited on 05/15/2024).
- [3] The L^AT_EX Project. *The L^AT_EX3 kernel. Style guide for code authors*. The referenced version of the document is attached to this document. Apr. 11, 2024. URL: <http://mirrors.ctan.org/macros/latex/required/l3kernel/l3styleguide.pdf> (visited on 05/08/2024).
- [4] The L^AT_EX Project. *The expl3 package and L^AT_EX3 programming*. The referenced version of the document is attached to this document. Apr. 11, 2024. URL: <http://mirrors.ctan.org/macros/latex/required/l3kernel/exp13.pdf> (visited on 05/08/2024).
- [5] Joseph Wright. Apr. 29, 2024. URL: <https://github.com/latex3/latex3/pull/1542#issuecomment-2082352499> (visited on 05/15/2024).

Index

E

E102, 5
E104, 6
E201, 6
E203, 7
E208, 8
E209, 9
E300, 9
E301, 9
E504, 12
E505, 12
E507, 13
E508, 13
E511, 14
E513, 15
E514, 15
E515, 15
E516, 16
E517, 16
E521, 18
E522, 18
E523, 18
E524, 19
E600, 19
E603, 21
E604, 21

E606, 22
E607, 23
E608, 23
E611, 25
E612, 25
E614, 26
E615, 26
E617, 27
E618, 27
E619, 28
E620, 29
E621, 29
E625, 31

S

S103, 5
S204, 7
S205, 7
S206, 7
S207, 8

T

T500, 10
T503, 11
T518, 16
T623, 30

T624, 31

W

W100, 4
W101, 5
W200, 6
W202, 7
W302, 10
W303, 10
W501, 11
W502, 11
W506, 12
W509, 13
W510, 14
W512, 14
W519, 17
W520, 18
W601, 20
W602, 21
W605, 22
W609, 24
W610, 24
W613, 26
W616, 27
W622, 30
W626, 31