

CURLOPT\_DNS\_USE\_GLOBAL\_CACHE(3), curl\_easy\_setopt option, CURLOPT\_DNS\_USE\_GLOBAL\_CACHE(3)

## NAME

CURLOPT\_DNS\_USE\_GLOBAL\_CACHE – enable/disable global DNS cache

## SYNOPSIS

```
#include <curl/curl.h>
```

```
CURLcode curl_easy_setopt(CURL *handle, CURLOPT_DNS_USE_GLOBAL_CACHE,  
                           long enable);
```

## DESCRIPTION

Pass a long. If the *enable* value is 1, it tells curl to use a global DNS cache that will survive between easy handle creations and deletions. This is not thread-safe and this will use a global variable.

**WARNING:** this option is considered obsolete. Stop using it. Switch over to using the share interface instead! See *CURLOPT\_SHARE(3)* and *curl\_share\_init(3)*.

## DEFAULT

0

## PROTOCOLS

All

## EXAMPLE

TODO

## AVAILABILITY

Subject for removal in the future. Do not use!

## RETURN VALUE

Returns CURLE\_OK if the option is supported, and CURLE\_UNKNOWN\_OPTION if not.

## SEE ALSO

CURLOPT\_SHARE(3), CURLOPT\_DNS\_CACHE\_TIMEOUT(3),